



Safety Data Sheet

Copyright, 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	20-0100-6	Version number:	9.02
Revision date:	10/10/2018	Supersedes date:	02/08/2018
Transportation version number: 2.00 (09/08/2015)			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Electronic Surfactant 4300

Product Identification Numbers

98-0212-3305-5 98-0212-3306-3

7100003756 7100038173

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Surfactant

Restrictions on Use

Prevent releases of surfactants to the environment. This includes, but is not limited to, treatment of surfactant containing aqueous waste streams. Contact 3M for additional information. One or more components in this material are approved for specific commercial use(s) under a U.S. EPA Low Volume Exemption. Approved commercial use(s) include: Surfactant in semiconductor manufacture and in industrial paints and coatings. Refer to Section 15 for additional information.

1.3. Details of the supplier of the safety data sheet

Address:	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone:	+44 (0)1344 858 000
E Mail:	tox.uk@mmm.com
Website:	www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Substance or Mixture Corrosive to Metals, Category 1 - Met. Corr. 1; H290

Flammable Liquid, Category 3 - Flam. Liq. 3; H226
 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
 Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
 Skin Sensitization, Category 1B - Skin Sens. 1B; H317

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS02 (Flame) | GHS05 (Corrosion) | GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Acetic acid	64-19-7	200-580-7	75 - 85
1-Propanesulfonic acid, 3-[hexyl[(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	606967-06-0		15 - 25

HAZARD STATEMENTS:

H290	May be corrosive to metals.
H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260A	Do not breathe vapours.
P280D	Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353A	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

Contains 25% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Acetic acid	64-19-7	200-580-7		75 - 85	Flam. Liq. 3, H226; Skin Corr. 1A, H314 - Nota B
1-Propanesulfonic acid, 3-[hexyl[(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	606967-06-0			15 - 25	Eye Dam. 1, H318; Skin Sens. 1B, H317

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products**Substance**

Acetic acid
Carbonyl fluoride.
Carbon monoxide.

Condition

During combustion.
During combustion.
During combustion.

Carbon dioxide.	During combustion.
Hydrogen Fluoride	During combustion.
Irritant vapours or gases.	During combustion.
Ammonia	During combustion.
Oxides of nitrogen.	During combustion.
Oxides of sulphur.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR-AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid inhalation of thermal decomposition products. For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Clear white or light yellow liquid with acetic acid odour.
Odour threshold	No data available.
pH	3.4 [Details: 1% aqueous]
Boiling point/boiling range	117.8 °C
Melting point	Not applicable.
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	38.9 °C [Test Method: Closed Cup]
Autoignition temperature	240.6 °C
Flammable Limits(LEL)	5.4 %
Flammable Limits(UEL)	16 %
Vapour pressure	2,026.5 Pa [@ 20 °C]
Relative density	1.1 [Ref Std: WATER=1]
Water solubility	100 %
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	No data available.
Decomposition temperature	No data available.
Viscosity	5 mPa-s [@ 25 °C]
Density	1.1 g/ml

9.2. Other information

Average particle size	No data available.
Bulk density	No data available.
EU Volatile Organic Compounds	880 g/l
Molecular weight	No data available.
Percent volatile	80 %
Softening point	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

3M™ Electronic Surfactant 4300

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Blood effects: Signs/symptoms may include generalised weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and hemoglobinemia. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE1,000 - 2,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE10 - 20 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Acetic acid	Dermal	Rabbit	LD50 1,060 mg/kg
Acetic acid	Inhalation-Vapour (4 hours)	Rat	LC50 11.4 mg/l
Acetic acid	Ingestion	Rat	LD50 3,310 mg/kg
1-Propanesulfonic acid, 3-[hexyl(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
1-Propanesulfonic acid, 3-[hexyl(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Acetic acid	Rabbit	Corrosive
1-Propanesulfonic acid, 3-[hexyl(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Acetic acid	Rabbit	Corrosive
1-Propanesulfonic acid, 3-[hexyl(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
1-Propanesulfonic acid, 3-[hexyl(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	Mouse	Sensitising

Respiratory Sensitisation

Name	Species	Value
Acetic acid	Human	Not classified

3M™ Electronic Surfactant 4300**Germ Cell Mutagenicity**

Name	Route	Value
Acetic acid	In Vitro	Not mutagenic
1-Propanesulfonic acid, 3-[hexyl[(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Acetic acid	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Acetic acid	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Acetic acid	Ingestion	Not classified for development	Rat	NOAEL 80 mg/kg/day	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Acetic acid	Inhalation	respiratory system	Causes damage to organs	Human	NOAEL Not available	not applicable
Acetic acid	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Acetic acid	Ingestion	blood kidney and/or bladder	Causes damage to organs	Human	NOAEL Not available	not applicable

Specific Target Organ Toxicity - repeated exposure

For the component/components, either no data is currently available or the data is not sufficient for classification.

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Acetic acid	64-19-7	Diatom	Estimated	72 hours	EC50	>306 mg/l

3M™ Electronic Surfactant 4300

Acetic acid	64-19-7	Water flea	Experimental	24 hours	EC50	6,000 mg/l
Acetic acid	64-19-7	Western Mosquitofish	Experimental	96 hours	LC50	251 mg/l
Acetic acid	64-19-7	Diatom	Estimated	72 hours	NOEC	306 mg/l
Acetic acid	64-19-7	Fish	Experimental	90 days	No obs Effect Level	1.26 mg/l
Acetic acid	64-19-7	Water flea	Experimental	21 days	NOEC	31.4 mg/l
1-Propanesulfonic acid, 3-[hexyl[(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	606967-06-0		Data not available or insufficient for classification			

12.2. Persistence and degradability

No test data available.

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Acetic acid	64-19-7	Experimental Bioconcentration		Log Kow	-0.17	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

Material	CAS Nbr	Ozone Depletion Potential	Global Warming Potential
1-propanesulfonic acid, 3-[hexyl[(nonafluorobutyl)sulfonyl]amino]-2-hydroxy-, monoammonium salt	606967-06-0	0	

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include HF. Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

200114* Acids

SECTION 14: Transportation information

98-0212-3305-5

ADR/RID: UN2789, ACETIC ACID SOLUTION, 8, (3), II, (D/E), ADR Classification Code: CF1.

IMDG-CODE: UN2789, ACETIC ACID SOLUTION, 8., (3.), II, IMDG-Code segregation code: 1 - ACIDS, EMS: FE,SC.

ICAO/IATA: UN2789, ACETIC ACID SOLUTION, 8, (3), II.

98-0212-3306-3

ADR/RID: UN2789, ACETIC ACID SOLUTION, LIMITED QUANTITY, 8, (3), II, (E), ADR Classification Code: CF1.

IMDG-CODE: UN2789, ACETIC ACID SOLUTION, 8., (3.), II, IMDG-Code segregation code: 1 - ACIDS, LIMITED QUANTITY, EMS: FE,SC.

ICAO/IATA: UN2789, ACETIC ACID SOLUTION, 8, (3), II.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Revision information:

Section 1: Restrictions on use information information was modified.

Section 5: Fire - Advice for fire fighters information information was modified.

Section 7: Precautions safe handling information information was modified.

Section 9: Property description for optional properties information was modified.

Section 10: Materials and conditions to avoid physical property information was deleted.

Section 12: Component ecotoxicity information information was modified.

Section 13: 13.1. Waste disposal note information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk