



## Safety Data Sheet

Copyright, 2017, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	16-3531-7	<b>Version number:</b>	19.02
<b>Revision date:</b>	08/09/2017	<b>Supersedes date:</b>	19/01/2017
<b>Transportation version number:</b> 3.00 (20/12/2016)			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M™ Fluorosurfactant FC-4432

#### Product Identification Numbers

98-0212-3045-7

7000006322

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Industrial use.

#### 1.3. Details of the supplier of the safety data sheet

<b>Address:</b>	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
<b>Telephone:</b>	+44 (0)1344 858 000
<b>E Mail:</b>	tox.uk@mmm.com
<b>Website:</b>	www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

**3M™ Fluorosurfactant FC-4432****Symbols:**

GHS09 (Environment) |

**Pictograms****HAZARD STATEMENTS:**

H411 Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS****Prevention:**

P273 Avoid release to the environment.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SUPPLEMENTAL INFORMATION****Supplemental Hazard Statements:**

EUH208 Contains 2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate. May produce an allergic reaction.

Contains 6% of components with unknown hazards to the aquatic environment.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester,telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3			82 - 92	Aquatic Chronic 2, H411
Polyether Polymer	Trade Secret			< 6	Substance not classified as hazardous
(2-Methoxymethylethoxy)propanol	34590-94-8	252-104-2	01-2119450011-60	< 5	Substance with a Community level exposure limit in the workplace
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	67584-55-8	266-733-5		< 1	Skin Sens. 1B, H317; Aquatic Chronic 2, H411
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-	34454-97-2	252-043-1		< 1	Repr. 2, H361d; STOT

**3M™ Fluorosurfactant FC-4432**

hydroxyethyl)-N-methylbutane-1-sulphonamide					SE 2, H371; STOT RE 2, H373
Toluene	108-88-3	203-625-9		< 0.8	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; Repr. 2, H361d; STOT SE 3, H336; STOT RE 2, H373 Aquatic Chronic 3, H412 Eye Irrit. 2, H319
1-butan Sulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4			< 0.1	Acute Tox. 4, H302; Eye Irrit. 2, H319; Repr. 2, H361df; Aquatic Chronic 2, H411

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you are concerned, get medical advice.

**Skin contact**

Wash with soap and water. If you are concerned, get medical advice.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1 Information on toxicological effects

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide.  
Carbon dioxide.  
Hydrogen Fluoride  
Oxides of nitrogen.

**Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.

Oxides of sulphur.

During combustion.

### **5.3. Advice for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### **6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

### **6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Avoid inhalation of thermal decomposition products. Avoid skin contact with hot material. For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### **7.2. Conditions for safe storage including any incompatibilities**

Keep container tightly closed. Store away from oxidising agents. Store away from areas where product may come into contact with food or pharmaceuticals.

### **7.3. Specific end use(s)**

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available

for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Toluene	108-88-3	UK HSC	TWA: 191 mg/m <sup>3</sup> (50 ppm); STEL: 384 mg/m <sup>3</sup> (100 ppm)	SKIN
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	34454-97-2	Manufacturer determined	TWA: 1 mg/m <sup>3</sup> (0.07 ppm)	SKIN
(2-Methoxymethylethoxy)propanol	34590-94-8	UK HSC	TWA: 308 mg/m <sup>3</sup> (50 ppm)	SKIN
1-butanethiol, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4	Manufacturer determined	TWA: 0.5 mg/m <sup>3</sup> (0.04 ppm)	SKIN

UK HSC : UK Health and Safety Commission  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

<b>Material</b>	<b>Thickness (mm)</b>	<b>Breakthrough Time</b>
Polymer laminate	No data available	No data available

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Liquid.
Appearance/Odour	Viscous clear to cloudy amber with a slight mercaptan odour.
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Boiling point/boiling range	$\geq 110\text{ }^{\circ}\text{C}$
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	Flash point $> 93\text{ }^{\circ}\text{C}$ (200 $^{\circ}\text{F}$ )
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	38.7 Pa [ <i>Details:CONDITIONS: @ 20C</i> ]
Relative density	1.3 [ <i>Ref Std:WATER=1</i> ]
Water solubility	6.211 mg/ml
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	4.1 [ <i>Ref Std: AIR=1</i> ]
Decomposition temperature	<i>No data available.</i>
Viscosity	2,500 - 7,000 mPa-s
Density	1.3 g/ml

### 9.2. Other information

EU Volatile Organic Compounds	75.4 g/l
Molecular weight	<i>No data available.</i>
Percent volatile	$\leq 1\%$

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

None known.

**10.5 Incompatible materials**

Strong oxidising agents.

**10.6 Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

**SECTION 11: Toxicological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

May cause additional health effects (see below).

**Skin contact**

Contact with the skin during product use is not expected to result in significant irritation.

**Eye contact**

Vapours from heated material may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester, telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	Dermal	Rat	LD50 > 2,000 mg/kg

**3M™ Fluorosurfactant FC-4432**

2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester,telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	Ingestion	Rat	LD50 > 2,000 mg/kg
Polyether Polymer	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Polyether Polymer	Ingestion	Rat	LD50 5,700 mg/kg
(2-Methoxymethylethoxy)propanol	Dermal	Rabbit	LD50 > 19,000 mg/kg
(2-Methoxymethylethoxy)propanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
(2-Methoxymethylethoxy)propanol	Ingestion	Rat	LD50 5,180 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Ingestion	Rat	LD50 > 2,000 mg/kg
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	Dermal	Rat	LD50 > 2,000 mg/kg
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Ingestion	Rat	LD50 200-2000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
(2-Methoxymethylethoxy)propanol	Human and animal	No significant irritation
Toluene	Rabbit	Irritant
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Rabbit	No significant irritation
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	Rabbit	No significant irritation
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
(2-Methoxymethylethoxy)propanol	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Rabbit	Mild irritant
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	Rabbit	Mild irritant
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Rabbit	Severe irritant

**Skin Sensitisation**

Name	Species	Value
Overall product	Guinea pig	Not classified
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester,telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	Guinea pig	Not classified
(2-Methoxymethylethoxy)propanol	Human	Not classified
Toluene	Guinea pig	Not classified
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Guinea pig	Not classified
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	Guinea	Sensitising



**3M™ Fluorosurfactant FC-4432**

	pig	
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester,telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate, (2-Methoxymethylethoxy)propanol	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	In Vitro	Not mutagenic
2-[Methyl[(nonafluorobutyl)sulfonyl]amino]ethyl acrylate	In Vitro	Not mutagenic
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
(2-Methoxymethylethoxy)propanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 1.82 mg/l	during organogenesis
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	premating & during gestation
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 250 mg/kg/day	premating & during gestation
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	premating & during gestation
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Ingestion	Toxic to reproduction and/or development	Rat	NOAEL 150 mg/kg	
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Ingestion	Toxic to female reproduction	Rat	NOAEL 150 mg/kg/day	premating & during gestation
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Ingestion	Toxic to male reproduction	Rat	NOAEL 150 mg/kg/day	28 days
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Ingestion	Toxic to development	Rat	NOAEL 150 mg/kg/day	premating & during

**3M™ Fluorosurfactant FC-4432**

					gestation
--	--	--	--	--	-----------

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
(2-Methoxymethylethoxy)propanol	Dermal	central nervous system depression	Not classified	Rabbit	NOAEL 2,850 mg/kg	
(2-Methoxymethylethoxy)propanol	Inhalation	central nervous system depression	Not classified	Rat	LOAEL 3.07 mg/l	7 hours
(2-Methoxymethylethoxy)propanol	Ingestion	central nervous system depression	Not classified	Rat	LOAEL 5,000 mg/kg	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Ingestion	nervous system	May cause damage to organs	Rat	LOAEL 2,000 mg/kg	not applicable
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Ingestion	nervous system	Not classified	Rat	NOAEL 200 mg/kg	not applicable

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester, telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	Ingestion	heart   endocrine system   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
(2-Methoxymethylethoxy)propanol	Dermal	kidney and/or bladder   heart   endocrine system   hematopoietic system   liver   respiratory system	Not classified	Rabbit	NOAEL 9,500 mg/kg/day	90 days
(2-Methoxymethylethoxy)propanol	Inhalation	heart   hematopoietic system   liver   immune system   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1.21 mg/l	90 days
(2-Methoxymethylethoxy)propanol	Ingestion	liver   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   kidney	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**3M™ Fluorosurfactant FC-4432**

		and/or bladder   respiratory system				
Toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Ingestion	liver	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 50 mg/kg/day	28 days
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 50 mg/kg/day	28 days
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	Ingestion	kidney and/or bladder   heart   endocrine system   hematopoietic system   nervous system   respiratory system	Not classified	Rat	NOAEL 250 mg/kg/day	28 days
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	premating & during gestation
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	Ingestion	hematopoietic system   liver   immune system   heart   endocrine system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

**Aspiration Hazard**

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonylamino]ethyl ester,telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3	Water flea	Experimental	48 hours	EC50	99 mg/l
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonylamino]ethyl ester,telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3	Diatom	Experimental	72 hours	EC50	3.24 mg/l
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonylamino]ethyl ester,telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3	Fish	Experimental	96 hours	LC50	>3.2 mg/l
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonylamino]ethyl ester,telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonylamino]ethyl ester,telomer with 3-	1017237-78-3	Fathead minnow	Experimental	96 hours	LC50	765 mg/l

**3M™ Fluorosurfactant FC-4432**

mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,						
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester, telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3	Copepods	Experimental	48 hours	EC50	132 mg/l
Polyether Polymer	Trade Secret		Data not available or insufficient for classification			
(2-Methoxymethylethoxy) propanol	34590-94-8	Fathead minnow	Experimental	96 hours	LC50	>10,000 mg/l
(2-Methoxymethylethoxy) propanol	34590-94-8	Water flea	Experimental	48 hours	EC50	1,919 mg/l
(2-Methoxymethylethoxy) propanol	34590-94-8	Green Algae	Experimental	72 hours	EC50	>969 mg/l
(2-Methoxymethylethoxy) propanol	34590-94-8	Green Algae	Experimental	72 hours	Effect Concentration 10%	133 mg/l
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	34454-97-2	Fathead minnow	Experimental	96 hours	LC50	25 mg/l
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	34454-97-2	Crustacea other	Experimental	96 hours	EC50	4.4 mg/l
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	34454-97-2	Green Algae	Experimental	72 hours	EC50	79 mg/l
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	34454-97-2	Green Algae	Experimental	72 hours	NOEC	21 mg/l
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	67584-55-8	Water flea	Experimental	48 hours	EC50	1.2 mg/l
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	67584-55-8	Green algae	Experimental	72 hours	NOEC	0.34 mg/l
Toluene	108-88-3	Fish other	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l

**3M™ Fluorosurfactant FC-4432**

Toluene	108-88-3	Coho salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4	Green Algae	Experimental	96 hours	EC50	13 mg/l
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4	Mysid Shrimp	Experimental	96 hours	EC50	2.4 mg/l
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4	Fathead minnow	Experimental	96 hours	LC50	44 mg/l
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4	Green Algae	Experimental	96 hours	NOEC	1.9 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester, telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3	Experimental Biodegradation	28 days	BOD	3 % weight	OECD 301D - Closed bottle test
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester, telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3	Experimental Hydrolysis		Hydrolytic half-life	48.5 years (t 1/2)	Other methods
Polyether Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
(2-Methoxymethylethoxy)propanol	34590-94-8	Experimental Biodegradation	28 days	BOD	75 % weight	OECD 301F - Manometric respirometry
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	34454-97-2	Experimental Biodegradation	28 days	CO2 evolution	2 % weight	OECD 301B - Modified sturm or CO2
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	67584-55-8	Experimental Aquatic Biodegrad. - Aerobic	28 days	% CO2 produced	2 % weight	OECD 301B - Modified sturm or CO2
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	67584-55-8	Experimental Hydrolysis		Hydrolytic half-life	0.6 years (t 1/2)	Other methods
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % weight	
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	Other methods
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4	Estimated Photolysis		Photolytic half-life (in air)	25.2 days (t 1/2)	Other methods
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4	Estimated Biodegradation	28 days	BOD	0 % weight	Estimated: MITI biodegradability tests

**12.3 : Bioaccumulative potential**

**3M™ Fluorosurfactant FC-4432**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-Propenoic acid, 2-[methyl[(1,1,2,2,3,3,4,4,4-nonafluorobutyl)sulfonyl]amino]ethyl ester, telomer with 3-mercapto-1,2-propanediol, 2-methyloxirane polymer with oxirane di-2-propenoate,	1017237-78-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyether Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
(2-Methoxymethylethoxy)propanol	34590-94-8	Experimental Bioconcentration		Log Kow	0.0061	Other methods
1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-hydroxyethyl)-N-methylbutane-1-sulphonamide	34454-97-2	Estimated Bioconcentration		Log Kow	2.83	Estimated: Bioconcentration factor
2-[Methyl[(nonafluorobutyl)sulphonyl]amino]ethyl acrylate	67584-55-8	Estimated Bioconcentration		Bioaccumulation factor	5	Other methods
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	Other methods
1-butanedisulphonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-N-methyl-	68298-12-4	Estimated Bioconcentration		Bioaccumulation factor	970	Estimated: Bioconcentration factor

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

No information available at this time, contact manufacturer for more details

**12.6. Other adverse effects**

No information available.

## SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

070103*	Organic halogenated solvents, washing liquids and mother liquors
14 06 02*	Other halogenated solvents and solvent mixtures

**SECTION 14: Transportation information**

98-0212-3045-7

**ADR/RID:** UN3082, NOT RESTRICTED AS PER SPECIAL PROVISION 375, ENVIRONMENTALLY HAZARDOUS SUBSTANCE EXEMPTION, III, --.

**IMDG-CODE:** UN3082, NOT RESTRICTED AS PER IMDG CODE 2.10.2.7, MARINE POLLUTANT EXCEPTION, III, IMDG-Code segregation code: NONE, EMS: --.

**ICAO/IATA:** UN3082, NOT RESTRICTED AS PER SPECIAL PROVISION A197, ENVIRONMENTALLY HAZARDOUS SUBSTANCE EXCEPTION, III.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity****Ingredient**

Toluene

**CAS Nbr**

108-88-3

**Classification**

Gr. 3: Not classifiable

**Regulation**International Agency  
for Research on Cancer**Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

**15.2. Chemical Safety Assessment**

Not applicable

**SECTION 16: Other information****List of relevant H statements**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361df	Suspected of damaging fertility. Suspected of damaging the unborn child.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.



H412 Harmful to aquatic life with long lasting effects.

**Revision information:**

Section 3: Composition/ Information of ingredients table information was added.

Section 3: Composition/ Information of ingredients table information was deleted.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Biocumulative potential information information was modified.

Section 13: Standard Phrase Category Waste GHS information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M United Kingdom MSDSs are available at [www.3M.com/uk](http://www.3M.com/uk)**