



Safety Data Sheet

Copyright, 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 08-1308-9 **Version number:** 22.00
Revision date: 04/10/2018 **Supersedes date:** 24/08/2018
Transportation version number: 1.00 (02/03/2011)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Novec™ 7200 Engineered Fluid

| REACH registration number | CASRN | EC Number | Ingredient Name |
|---------------------------|-------|-----------|---|
| 01-0000017174-74-0003 | | 425-340-0 | Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane |

Product Identification Numbers

98-0211-9363-0 98-0211-9367-1 98-0211-9368-9 XA-0077-9076-0

7100003770 7100003769 7100003768

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

For industrial use only. Not intended for use as a medical device or drug.

Restrictions on Use

Novec™ Engineered Fluids are used in a wide variety of applications, including but not limited to precision cleaning of medical devices and as lubricant deposition solvents for medical devices. When the product is used for applications where the finished device is implanted into the human body, no residual Novec solvent may remain on the parts. It is highly recommended that the supporting test results and protocol be cited during FDA registration.

3M Electronics Markets Materials Division (EMMD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMMD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

1.3. Details of the supplier of the safety data sheet

3M™ Novec™ 7200 Engineered Fluid

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification**2.1. Classification of the substance or mixture**

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Hazardous to the Aquatic Environment (Chronic), Category 4 - Aquatic Chronic 4; H413

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Ingredients:

| Ingredient | CAS Nbr | EC No. | % by Wt |
|---|---------|-----------|----------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | 425-340-0 | 80 - 100 |

HAZARD STATEMENTS:

H413 May cause long lasting harmful effects to aquatic life.

PRECAUTIONARY STATEMENTS**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SUPPLEMENTAL INFORMATION**Supplemental Hazard Statements:**

EUH018 In use, may form flammable/explosive vapour-air mixture.

Notes on labelling

Updated per Regulation (EC) No. 648/2004 on detergents.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

| Ingredient | CAS Nbr | EC No. | REACH Registration No. | % by Wt | Classification |
|---------------------|---------|-----------|------------------------|----------|-----------------|
| Reaction Mass of 2- | | 425-340-0 | | 80 - 100 | Aquatic Chronic |

3M™ Novec™ 7200 Engineered Fluid

| | | | | | |
|--|--|--|--|--|---------|
| (ethoxydifluoromethyl)- 1,1,1,2,3,3,3- heptafluoropropane and 1- ethoxy-1,1,2,2,3,3,4,4,4- nonafluoro-butane | | | | | 4, H413 |
|--|--|--|--|--|---------|

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If you feel unwell, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

3M™ Novec™ 7200 Engineered Fluid

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid inhalation of thermal decomposition products. Avoid skin contact with hot material. For industrial or professional use only. Store work clothes separately from other clothing, food and tobacco products. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

| Ingredient | Degradation Product | Population | Human exposure pattern | DNEL |
|---|---------------------|------------|--|-------------------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | Worker | Inhalation, Long-term exposure (8 hours), Systemic effects | 1,764 mg/m ³ |

Predicted no effect concentrations (PNEC)

| Ingredient | Degradation Product | Compartment | PNEC |
|---|---------------------|------------------------|--------------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | Agricultural soil | 0.0041 mg/kg d.w. |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | Air average | mg/m ³ |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | Freshwater | 0.00237 mg/l |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | Freshwater sediments | 0.0393 mg/kg d.w. |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | Grassland average | 0.0041 mg/kg d.w. |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | Marine water | 0.000237 mg/l |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | Marine water sediments | 0.00393 mg/kg d.w. |

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

| Material | Thickness (mm) | Breakthrough Time |
|-----------------|-------------------|-------------------|
| Nitrile rubber. | No data available | No data available |

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Respiratory protection

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

Applicable Norms/Standards

Use gloves tested to EN 407

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------------------|--|
| Physical state | Liquid. |
| Specific Physical Form: | liquid |
| Appearance/Odour | Clear colourless liquid with faint odour |
| Odour threshold | <i>No data available.</i> |
| pH | <i>Not applicable.</i> |
| Boiling point/boiling range | 76 °C |
| Melting point | -138 °C |

| | |
|---|---|
| Flammability (solid, gas) | Not applicable. |
| Explosive properties | Not classified |
| Oxidising properties | Not classified |
| Flash point | No flash point |
| Autoignition temperature | 375 °C [<i>Details:</i> ASTM E659-78 Method] |
| Flammable Limits(LEL) | 210 g/m ³ [<i>Details:</i> ASTM E681-94 Method] |
| Flammable Limits(UEL) | 1,070 g/m ³ [<i>Details:</i> ASTM E681-94 Method] |
| Vapour pressure | 14,532.1 Pa [<i>@ 25 °C</i>] |
| Relative density | 1.43 [<i>Ref Std:</i> WATER=1] |
| Water solubility | Nil |
| Solubility- non-water | <i>No data available.</i> |
| Partition coefficient: n-octanol/water | 4.2 [<i>Details:</i> at 30 °C] |
| Evaporation rate | 33 [<i>Ref Std:</i> BUOAC=1] |
| Vapour density | 9.1 [<i>Ref Std:</i> AIR=1] |
| Decomposition temperature | <i>Not applicable.</i> |
| Viscosity | 0.4 mm ² /sec |
| Density | 1.43 g/ml |

9.2. Other information

| | |
|--------------------------------------|---------------------------|
| EU Volatile Organic Compounds | 1,430 g/l |
| Molecular weight | <i>No data available.</i> |
| Percent volatile | 100 % |

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong acids.
Strong bases.
Strong oxidising agents.

10.6 Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------------------|--|
| Hydrogen Fluoride | At elevated temperatures. - extreme conditions of heat |
| Perfluoroisobutylene (PFIB). | At elevated temperatures. - extreme conditions of heat |

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme conditions of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

May be harmful in contact with skin.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|-----------------------------|---------|--|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane | Dermal | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane | Inhalation-Vapour (4 hours) | Rat | LC50 > 989 mg/l |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane | Ingestion | Rat | > 2,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane | Rabbit | No significant irritation |

Skin Sensitisation

| Name | Species | Value |
|--|---------|----------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and | Guinea | Not classified |

3M™ Novec™ 7200 Engineered Fluid

| | |
|--|-----|
| 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | pig |
|--|-----|

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|---------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | In Vitro | Not mutagenic |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | In vivo | Not mutagenic |

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|------------|--------------------------------|---------|----------------|-------------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | Inhalation | Not classified for development | Rat | NOAEL 260 mg/l | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|------------|------------------------|--|---------|----------------|-------------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | Inhalation | cardiac sensitisation | Some positive data exist, but the data are not sufficient for classification | Dog | NOAEL 204 mg/l | 17 minutes |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | Inhalation | respiratory irritation | Not classified | Rat | NOAEL 989 mg/l | 4 hours |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|------------|--|----------------|---------|-----------------------|-------------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | Inhalation | liver kidney and/or bladder respiratory system heart endocrine system gastrointestinal tract bone marrow hematopoietic system immune system nervous system | Not classified | Rat | NOAEL 263.4 mg/l | 4 weeks |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | Ingestion | blood liver kidney and/or bladder heart endocrine system bone marrow hematopoietic system immune system nervous system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |

3M™ Novec™ 7200 Engineered Fluid

| | | | | | | |
|--|--|-----------------------------|--|--|--|--|
| | | system respiratory system | | | | |
|--|--|-----------------------------|--|--|--|--|

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

| Material | CAS # | Organism | Type | Exposure | Test endpoint | Test result |
|---|-----------|----------------|----------------------|----------|--------------------------|-------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | 425-340-0 | Water flea | Experimental | 48 hours | EC50 | >100 mg/l |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | 425-340-0 | Green algae | Endpoint not reached | 72 hours | EC50 | >100 mg/l |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | 425-340-0 | Fathead minnow | Experimental | 96 hours | LC50 | >100 mg/l |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | 425-340-0 | Green algae | Experimental | 72 hours | Effect Concentration 10% | 2.37 mg/l |

12.2. Persistence and degradability

| Material | CAS Nbr | Test type | Duration | Study Type | Test result | Protocol |
|---|-----------|-----------------------------|----------|-------------------------------|--------------------|--------------------------------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | 425-340-0 | Experimental Photolysis | | Photolytic half-life (in air) | 0.55 years (t 1/2) | Other methods |
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1- | 425-340-0 | Experimental Biodegradation | 28 days | BOD | 0 % BOD/ThBOD | OECD 301D - Closed bottle test |

3M™ Novec™ 7200 Engineered Fluid

| | | | | | | |
|--|--|--|--|--|--|--|
| ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | | | | | | |
|--|--|--|--|--|--|--|

12.3 : Bioaccumulative potential

| Material | Cas No. | Test type | Duration | Study Type | Test result | Protocol |
|---|-----------|---|----------|------------|-------------|----------|
| Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane | 425-340-0 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

070103* Organic halogenated solvents, washing liquids and mother liquors
14 06 02* Other halogenated solvents and solvent mixtures

SECTION 14: Transportation information

98-0211-9363-0, 98-0211-9367-1, 98-0211-9368-9

Not hazardous for transportation

XA-0077-9076-0

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

3M™ Novec™ 7200 Engineered Fluid

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment

A chemical safety assessment has been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H413 May cause long lasting harmful effects to aquatic life.

Revision information:

Industrial Handling of Heat Transfer, Cooling, and Dielectric Fluid: Section 16: Annex information was added.

Industrial Laboratory Use: Section 16: Annex information was added.

Industrial Use as a Solvent: Section 16: Annex information was added.

Industrial Use in Vapour Degreasing Systems: Section 16: Annex information was added.

Laboratory Use: Section 16: Annex information was added.

Professional Handling of Heat Transfer Fluid: Section 16: Annex information was added.

Professional Use as a Solvent: Section 16: Annex information was added.

Section 8: 8.2. Exposure controls information information was added.

Section 8: 8.2.3. Environmental exposure controls information information was added.

Section 8: DNEL table row information was added.

Section 8: PNEC table row information was added.

Section 12: Component ecotoxicity information information was modified.

Annex: Prediction of exposure statement information was added.

Annex

| 1. Title | |
|--|--|
| Substance identification | Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,3,4,4,4-nonafluoro-butane; EC No. 425-340-0; |
| Exposure Scenario Name | Industrial Handling of Heat Transfer, Cooling, and Dielectric Fluid |
| Lifecycle Stage | Use at industrial sites |
| Contributing activities | PROC 01 -Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities ERC 07 -Use of functional fluid at industrial site |
| Processes, tasks and activities covered | Draining process equipment. Transfers with dedicated controls, including loading, filling, dumping, bagging. Transfers without dedicated controls, including loading, filling, dumping, bagging. Use as heat transfer fluids. |
| 2. Operational conditions and risk management measures | |

3M™ Novec™ 7200 Engineered Fluid

| | |
|----------------------------------|--|
| Operating Conditions | <p>Physical state:Liquid. General operating conditions: Continuous process; Discharge volume of sewage treatment plant: <= 2,000,000 liters per day; Emission days per year: 365 days/year; Flow rate of receiving surface water:: <= 18,000 cubic meters per day; Fraction of applied product lost from process/use to solid waste in percent: 99.95 %; Fraction of applied product lost from process/use to waste: 0.0005 ; Fraction of applied product lost from process/use to waste gas: 0.0005 ; Fraction of applied product lost from process/use to waste water: 0 ; Fraction of product consumed in process/use: 0 ; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;</p> |
| Risk management measures | <p>Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;</p> |
| Waste management measures | Incinerate in a facility capable of handling halogenated waste; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.Contact 3M at the address or phone number listed on the first page of the SDS for information on exposure estimation. |

| | |
|---|--|
| 1. Title | |
| Substance identification | Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,3,4,4,4-nonafluoro-butane; EC No. 425-340-0; |
| Exposure Scenario Name | Industrial Laboratory Use |
| Lifecycle Stage | Widespread use by professional workers |
| Contributing activities | PROC 15 -Use a laboratory reagent ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) |
| Processes, tasks and activities covered | Use as a laboratory reagent. |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | <p>Physical state:Liquid. General operating conditions: Discharge volume of sewage treatment plant: <= 2,000,000 liters per day; Emission days per year: 300 days/year; Flow rate of receiving surface water:: <= 18,000 cubic meters per day; Fraction of applied product lost from process/use to solid waste in percent: 50 %; Fraction of applied product lost from process/use to waste: 1 ; Fraction of applied product lost from process/use to waste gas: 0.5 ; Fraction of applied product lost from process/use to waste water: 0 ; Fraction of product consumed in process/use: 0 ; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;</p> |
| Risk management measures | <p>Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health:</p> |

3M™ Novec™ 7200 Engineered Fluid

| | |
|----------------------------------|--|
| | None needed; Environmental: None needed; |
| Waste management measures | Incinerate in a facility capable of handling halogenated waste; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. Contact 3M at the address or phone number listed on the first page of the SDS for information on exposure estimation. |

| | |
|---|--|
| 1. Title | |
| Substance identification | Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane; EC No. 425-340-0; |
| Exposure Scenario Name | Industrial Use as a Solvent |
| Lifecycle Stage | Use at industrial sites |
| Contributing activities | PROC 05 -Mixing or blending in batch processes PROC 07 -Industrial spraying PROC 13 -Treatment of articles by dipping and pouring ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) |
| Processes, tasks and activities covered | Mixing operations (open systems). |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Discharge volume of sewage treatment plant: <= 2,000,000 liters per day; Emission days per year: 20 days per year; Flow rate of receiving surface water: <= 18,000 cubic meters per day; Fraction of applied product leaving the site with products: 0 ; Fraction of applied product lost from process/use to solid waste in percent: 0 %; Fraction of applied product lost from process/use to waste: 1 ; Fraction of applied product lost from process/use to waste gas: 1 ; Fraction of applied product lost from process/use to waste water: 0 ; Fraction of product consumed in process/use: 0 ; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed; |
| Waste management measures | Incinerate in a facility capable of handling halogenated waste; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. Contact 3M at the address or phone number listed on the first page of the SDS for information on exposure estimation. |

| | |
|---------------------------------|--|
| 1. Title | |
| Substance identification | Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane; |

3M™ Novec™ 7200 Engineered Fluid

| | |
|---|--|
| | EC No. 425-340-0; |
| Exposure Scenario Name | Industrial Use in Vapour Degreasing Systems |
| Lifecycle Stage | Use at industrial sites |
| Contributing activities | PROC 04 -Chemical production where opportunity for exposure arises PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) |
| Processes, tasks and activities covered | Transfers with dedicated controls, including loading, filling, dumping, bagging. |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Discharge volume of sewage treatment plant: <= 2,000,000 liters per day; Emission days per year: 300 days/year; Flow rate of receiving surface water:: <= 18,000 cubic meters per day; Fraction of applied product lost from process/use to solid waste in percent: 64.2 %; Fraction of applied product lost from process/use to waste: 1 ; Fraction of applied product lost from process/use to waste gas: 0.358 ; Fraction of applied product lost from process/use to waste water: 0 ; Fraction of product consumed in process/use: 0 ; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ; Partially open and partially closed process; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed; |
| Waste management measures | Incinerate in a facility capable of handling halogenated waste; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.Contact 3M at the address or phone number listed on the first page of the SDS for information on exposure estimation. |

| | |
|---|--|
| 1. Title | |
| Substance identification | Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,3,4,4,4-nonafluoro-butane; EC No. 425-340-0; |
| Exposure Scenario Name | Laboratory Use |
| Lifecycle Stage | Use at industrial sites |
| Contributing activities | PROC 15 -Use a laboratory reagent ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) |
| Processes, tasks and activities covered | Use as a laboratory reagent. |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Discharge volume of sewage treatment plant: <= 2,000,000 liters per day; Emission days per year: 300 days/year; Flow rate of receiving surface water:: <= 18,000 cubic meters per day; Fraction of applied product lost from process/use to solid waste in percent: 50 %; |

3M™ Novec™ 7200 Engineered Fluid

| | |
|----------------------------------|---|
| | <p>Fraction of applied product lost from process/use to waste: 1 ; Fraction of applied product lost from process/use to waste gas: 0.5 ; Fraction of applied product lost from process/use to waste water: 0 ; Fraction of product consumed in process/use: 0 ; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;</p> |
| Risk management measures | <p>Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;</p> |
| Waste management measures | <p>Incinerate in a facility capable of handling halogenated waste;</p> |
| 3. Prediction of exposure | |
| Prediction of exposure | <p>Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. Contact 3M at the address or phone number listed on the first page of the SDS for information on exposure estimation.</p> |

| | |
|---|--|
| 1. Title | |
| Substance identification | <p>Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane; EC No. 425-340-0;</p> |
| Exposure Scenario Name | <p>Professional Handling of Heat Transfer Fluid</p> |
| Lifecycle Stage | <p>Widespread use by professional workers</p> |
| Contributing activities | <p>PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities ERC 09a -Widespread use of functional fluid (indoor)</p> |
| Processes, tasks and activities covered | <p>Transfers without dedicated controls, including loading, filling, dumping, bagging.</p> |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | <p>Physical state:Liquid. General operating conditions: Continuous release; Discharge volume of sewage treatment plant: <= 2,000,000 liters per day; Emission days per year: 365 days/year; Flow rate of receiving surface water:: <= 18,000 cubic meters per day; Fraction of applied product lost from process/use to solid waste in percent: 99.95 %; Fraction of applied product lost from process/use to waste: 0.0005 ; Fraction of applied product lost from process/use to waste gas: 0.0005 ; Fraction of applied product lost from process/use to waste water: 0 ; Fraction of product consumed in process/use: 0 ; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;</p> |
| Risk management measures | <p>Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;</p> |
| Waste management measures | <p>Incinerate in a facility capable of handling halogenated waste;</p> |

3M™ Novec™ 7200 Engineered Fluid

| | |
|----------------------------------|--|
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. Contact 3M at the address or phone number listed on the first page of the SDS for information on exposure estimation. |

| | |
|---|--|
| 1. Title | |
| Substance identification | Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane; EC No. 425-340-0; |
| Exposure Scenario Name | Professional Use as a Solvent |
| Lifecycle Stage | Widespread use by professional workers |
| Contributing activities | PROC 10 -Roller application or brushing PROC 11 -Non industrial spraying PROC 13 -Treatment of articles by dipping and pouring PROC 19 -Manual activities involving hand contact ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) |
| Processes, tasks and activities covered | Cleaning surfaces by wiping, brushing. Immersion operations. Spraying of substances/mixtures. |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Discharge volume of sewage treatment plant: <= 2,000,000 liters per day; Emission days per year: 20 days per year; Flow rate of receiving surface water: <= 18,000 cubic meters per day; Fraction of applied product leaving the site with products: 0 ; Fraction of applied product lost from process/use to solid waste in percent: 0 %; Fraction of applied product lost from process/use to waste: 1 ; Fraction of applied product lost from process/use to waste gas: 1 ; Fraction of applied product lost from process/use to waste water: 0 ; Fraction of product consumed in process/use: 0 ; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed; |
| Waste management measures | Incinerate in a facility capable of handling halogenated waste; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. Contact 3M at the address or phone number listed on the first page of the SDS for information on exposure estimation. |

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk

