



Safety Data Sheet

Copyright, 2019, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	17-8391-9	Version number:	16.00
Revision date:	11/06/2019	Supersedes date:	07/06/2019
Transportation version number:	1.00 (05/01/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Novec™ 72DA Engineered Fluid

Product Identification Numbers

98-0212-3096-0 98-0212-3163-8

7100003761 7100024955

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

For Industrial Use Only. See Limitations on Use for supplemental information on intended applications including Medical Device applications.

Restrictions on Use

Novec™ Engineered Fluids are used in a wide variety of applications including but not limited to precision cleaning of medical devices and as a lubricant deposition solvent for medical devices. When the product is used for applications where the finished device is implanted into the human body, no residual Novec™ solvent may remain on the parts. It is highly recommended that the supporting test results and protocol be cited during FDA registration.

3M Electronics Markets Materials Division (EMMD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMMD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

1.3. Details of the supplier of the safety data sheet

Address:	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone:	+44 (0)1344 858 000
E Mail:	tox.uk@mmm.com
Website:	www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification**2.1. Classification of the substance or mixture****CLP REGULATION (EC) No 1272/2008****CLASSIFICATION:**

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements**CLP REGULATION (EC) No 1272/2008****SIGNAL WORD**

WARNING.

Symbols:

GHS07 (Exclamation mark) |

Pictograms**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
Trans-dichloroethylene	156-60-5	205-860-2	66 - 70

HAZARD STATEMENTS:

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P261A	Avoid breathing vapours.
-------	--------------------------

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
--------------------	--

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH018

In use, may form flammable/explosive vapour-air mixture.

Supplemental Precautionary Statements:

Vapours liberated during processing may be hazardous if inhaled. Eye, nose, throat and lung irritation can occur from such vapours.

Notes on labelling

H332 does not apply based on toxicity testing.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Trans-dichloroethylene	156-60-5	205-860-2	01-2120093504-55	66 - 70	Flam. Liq. 2, H225; Acute Tox. 4, H332; Aquatic Chronic 3, H412 - Nota C Eye Irrit. 2, H319; STOT SE 3, H336
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane		425-340-0	01-0000017174-74	15 - 25	Aquatic Chronic 4, H413
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane		422-270-2	01-0000016878-53	5 - 15	Substance not classified as hazardous
Propan-2-ol	67-63-0	200-661-7	01-2119457558-25	1 - 3	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If you feel unwell, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures
--

5.1. Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Contents may be under pressure, open carefully. Avoid inhalation of thermal decomposition products. Avoid skin contact with hot material. For industrial/occupational use only. Not for consumer sale or use. Store work clothes separately from other clothing, food and tobacco products. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store at temperatures not exceeding 38C/100F. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
trans-dichloroethylene	156-60-5	UK HSC	TWA:806 mg/m ³ (200 ppm);STEL:1010 mg/m ³ (250 ppm)	
Propan-2-ol	67-63-0	UK HSC	TWA:999 mg/m ³ (400 ppm);STEL:1250 mg/m ³ (500 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
Trans-dichloroethylene		Consumer	Inhalation, Long-term exposure (24 hours), Systemic effects	198 mg/m ³
Trans-dichloroethylene		Consumer	Oral, Long-term exposure (24 hours), Systemic effects	57 mg/kg bw/d
Trans-dichloroethylene		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	797 mg/m ³
Propan-2-ol		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	888 mg/kg bw/d

3M™ Novec™ 72DA Engineered Fluid

Propan-2-ol		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	500 mg/m ³
-------------	--	--------	--	-----------------------

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
Trans-dichloroethylene		Agricultural soil	0.0563 mg/kg d.w.
Trans-dichloroethylene		Freshwater	0.0364 mg/l
Trans-dichloroethylene		Freshwater sediments	0.5483 mg/kg d.w.
Trans-dichloroethylene		Grassland average	0.0563 mg/kg d.w.
Trans-dichloroethylene		Intermittent releases to water	0.3636 mg/l
Trans-dichloroethylene		Marine water	0.0036 mg/l
Trans-dichloroethylene		Marine water sediments	0.0548 mg/kg d.w.
Trans-dichloroethylene		Sewage Treatment Plant	17 mg/l
Propan-2-ol		Agricultural soil	28 mg/kg d.w.
Propan-2-ol		Concentration in marine fish for secondary poisoning	160 mg/kg w.w.
Propan-2-ol		Freshwater	140.9 mg/l
Propan-2-ol		Freshwater sediments	552 mg/kg d.w.
Propan-2-ol		Intermittent releases to water	140.9 mg/l
Propan-2-ol		Marine water	140.9 mg/l
Propan-2-ol		Marine water sediments	552 mg/kg d.w.
Propan-2-ol		Sewage Treatment Plant	2,251 mg/l

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Neoprene.	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Neoprene apron.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type A

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

Applicable Norms/Standards

Use gloves tested to EN 407

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Liquid.
Appearance/Odour	Clear colourless liquid with slight odour.
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Boiling point/boiling range	45 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	No flash point [<i>Details:</i> Tested according to ASTM Method D-3278-96 e-1]
Autoignition temperature	408 °C
Flammable Limits(LEL)	5.9 % volume [<i>Details:</i> Tested according to ASTM Method E681-98 (per Annex A1)]
Flammable Limits(UEL)	14.5 % volume [<i>Details:</i> Tested according to ASTM Method E681-98 (per Annex A1)]

Vapour pressure	47,995.9 Pa [@ 25 °C]
Relative density	1.27 [Ref Std: WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	2.26 [@ 25 °C] [Ref Std: AIR=1]
Decomposition temperature	Not applicable.
Viscosity	0.4 mPa-s
Density	1.27 g/ml

9.2. Other information

EU Volatile Organic Compounds	1,270 g/l
Molecular weight	No data available.
Percent volatile	100 %

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Hydrogen Chloride	At elevated temperatures. - extreme conditions of heat
Hydrogen Fluoride	At elevated temperatures. - extreme conditions of heat
Perfluoroisobutylene (PFIB).	At elevated temperatures. - extreme conditions of heat

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme conditions of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from

3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Trans-dichloroethylene	Dermal	Rabbit	LD50 > 5,000 mg/kg
Trans-dichloroethylene	Inhalation-Vapour (4 hours)	Rat	LC50 95.6 mg/l
Trans-dichloroethylene	Ingestion	Rat	LD50 7,902 mg/kg
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane	Inhalation-Vapour (4 hours)	Rat	LC50 > 989 mg/l
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane	Ingestion	Rat	> 2,000 mg/kg
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Dermal		LD50 estimated to be > 5,000 mg/kg
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Inhalation-Vapour (4 hours)	Rat	LC50 > 1,000 mg/l

3M™ Novec™ 72DA Engineered Fluid

Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Ingestion	Rat	LD50 > 5,000 mg/kg
Propan-2-ol	Dermal	Rabbit	LD50 12,870 mg/kg
Propan-2-ol	Inhalation-Vapour (4 hours)	Rat	LC50 72.6 mg/l
Propan-2-ol	Ingestion	Rat	LD50 4,710 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Trans-dichloroethylene	Rabbit	Minimal irritation
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Rabbit	No significant irritation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Rabbit	No significant irritation
Propan-2-ol	Multiple animal species	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Trans-dichloroethylene	Rabbit	Moderate irritant
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Rabbit	No significant irritation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Rabbit	No significant irritation
Propan-2-ol	Rabbit	Severe irritant

Skin Sensitisation

Name	Species	Value
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Guinea pig	Not classified
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Guinea pig	Not classified
Propan-2-ol	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Trans-dichloroethylene	In Vitro	Not mutagenic
Trans-dichloroethylene	In vivo	Not mutagenic
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	In Vitro	Not mutagenic
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	In vivo	Not mutagenic
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	In Vitro	Not mutagenic
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	In vivo	Not mutagenic
Propan-2-ol	In Vitro	Not mutagenic
Propan-2-ol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
------	-------	---------	-------

3M™ Novec™ 72DA Engineered Fluid

Propan-2-ol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
-------------	------------	-----	--

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Trans-dichloroethylene	Inhalation	Not classified for development	Rat	NOAEL 24 mg/l	during organogenesis
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Inhalation	Not classified for development	Rat	NOAEL 260 mg/l	during gestation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation
Propan-2-ol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Propan-2-ol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Trans-dichloroethylene	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Trans-dichloroethylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Trans-dichloroethylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 4,500 mg/kg	not applicable
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Inhalation	cardiac sensitisation	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 204 mg/l	17 minutes
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 989 mg/l	4 hours
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Inhalation	nervous system	Not classified	Dog	LOAEL 913 mg/l	10 minutes
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane	Inhalation	cardiac sensitisation	Not classified	Dog	NOAEL 913 mg/l	10 minutes

3M™ Novec™ 72DA Engineered Fluid

and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane						
Propan-2-ol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propan-2-ol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Propan-2-ol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Propan-2-ol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Trans-dichloroethylene	Inhalation	endocrine system liver kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 16 mg/l	90 days
Trans-dichloroethylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
Trans-dichloroethylene	Ingestion	blood liver	Not classified	Rat	NOAEL 125 mg/kg/day	14 weeks
Trans-dichloroethylene	Ingestion	heart immune system respiratory system	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Inhalation	liver kidney and/or bladder respiratory system heart endocrine system gastrointestinal tract bone marrow hematopoietic system immune system nervous system	Not classified	Rat	NOAEL 263.4 mg/l	4 weeks
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Ingestion	blood liver kidney and/or bladder heart endocrine system bone marrow hematopoietic system immune system nervous system respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Inhalation	heart skin endocrine system gastrointestinal tract hematopoietic system immune system muscles	Not classified	Rat	NOAEL 155 mg/l	13 weeks

3M™ Novec™ 72DA Engineered Fluid

methoxybutane		nervous system eyes kidney and/or bladder respiratory system				
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Ingestion	endocrine system liver heart hematopoietic system immune system nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Propan-2-ol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Propan-2-ol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Propan-2-ol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

Material	Organism	Type	Exposure	Test endpoint	Test result
3M™ Novec™ 72DA Engineered Fluid	Water flea	Calculated-Additive Toxicity	48 hours	EC50	>300 mg/l
3M™ Novec™ 72DA Engineered Fluid	Bluegill	Calculated-Additive Toxicity	96 hours	LC50	>190 mg/l

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	425-340-0	Green algae	Experimental	72 hours	Effect Concentration 10%	2.37 mg/l
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	422-270-2	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Propan-2-ol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l
Propan-2-ol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l

12.2. Persistence and degradability

3M™ Novec™ 72DA Engineered Fluid

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Trans-dichloroethylene	156-60-5	Experimental Photolysis		Photolytic half-life (in air)	13 days (t 1/2)	Other methods
Trans-dichloroethylene	156-60-5	Experimental Biodegradation	28 days	BOD	8 % weight	OECD 301D - Closed bottle test
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	425-340-0	Experimental Photolysis		Photolytic half-life (in air)	0.55 years (t 1/2)	Other methods
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	425-340-0	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301D - Closed bottle test
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	422-270-2	Experimental Photolysis		Photolytic half-life (in air)	2.9 years (t 1/2)	Other methods
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	422-270-2	Experimental Biodegradation	28 days	BOD	22 % BOD/ThBOD	OECD 301D - Closed bottle test
Propan-2-ol	67-63-0	Experimental Biodegradation	14 days	BOD	86 % BOD/ThBOD	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Trans-dichloroethylene	156-60-5	Experimental Bioconcentration		Log Kow	2.09	Other methods
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	422-270-2	Experimental Bioconcentration		Log Kow	4.0	Other methods
Propan-2-ol	67-63-0	Experimental Bioconcentration		Log Kow	0.05	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

070103* Organic halogenated solvents, washing liquids and mother liquors

SECTION 14: Transportation information

98-0212-3096-0, 98-0212-3163-8

Not hazardous for transportation

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. One or more of the components of this product have been notified to ELINCS (European List of Notified or New Chemical Substances). Certain restrictions apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Revision information:

Section 7: Conditions safe storage information was modified.

Section 8: Respiratory protection - recommended respirators information information was modified.

Section 11: Acute Toxicity table information was modified.

Annex

1. Title	
Substance identification	Trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Industrial Laboratory Use
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 15 -Use a laboratory reagent ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
Processes, tasks and activities covered	Use as a laboratory reagent.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use; Indoors with LEV and good general ventilation;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Industrial Use as a Solvent
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 07 -Industrial spraying PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 07 -Use of functional fluid at industrial site
Processes, tasks and activities covered	Cleaning process equipment and parts. Cleaning surfaces by wiping, brushing. Spraying of substances/mixtures. Transfer of substance/mixture with dedicated

	engineering controls. Transfer of substances/mixtures into small containers e.g. tubes, bottles or small reservoirs.
2. Operational conditions and risk management measures	
Operating Conditions	<p>Physical state:Liquid.</p> <p>General operating conditions: Discharge volume of sewage treatment plant: 2,000,000 liters per day; Emission days per year: 365 days per year; Flow rate of receiving surface water:: 18,000 cubic meters per day; Indoors with enhanced general ventilation; Indoors with good general ventilation; Large factory building (> 500 m³); Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;</p> <p>Task: Spraying; Duration of use: 4 hours/day;</p> <p>Task: Transferring Material; Duration of use: 4 hours/day;</p> <p>Task: Wiping Surfaces; Duration of use: 4 hours/day;</p>
Risk management measures	<p>Under the operational conditions described above the following risk management measures apply:</p> <p>General risk management measures: Human health: None needed; Environmental: None needed;</p>
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Industrial Use in Vapour Degreasing Systems
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 04 -Chemical production where opportunity for exposure arises PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 07 -Use of functional fluid at industrial site
Processes, tasks and activities covered	Draining process equipment. Transfer of substance/mixture with dedicated engineering controls. Vapour Degreasing
2. Operational conditions and risk management measures	
Operating Conditions	<p>Physical state:Liquid.</p> <p>General operating conditions: Discharge volume of sewage treatment plant: 2,000,000 liters per day; Duration of use: 8 hours/day; Emission days per year: 300 days per year; Flow rate of receiving surface water:: 18,000 cubic meters per day; Indoor use without Local Exhaust Ventilation;</p>

3M™ Novec™ 72DA Engineered Fluid

	Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ; Medium sized room or workshop (100 m ³ - 500 m ³); Partially open and partially closed process;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Incinerate in a facility capable of handling halogenated waste;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Propan-2-ol; EC No. 200-661-7; CAS Nbr 67-63-0;
Exposure Scenario Name	Industrial Use of Cleaners
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 04 -Chemical production where opportunity for exposure arises PROC 07 -Industrial spraying PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
Processes, tasks and activities covered	Application of product with a roller or brush. Spraying of substances/mixtures. Transfers with dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Assumes use at not more than 20°C above ambient temperature; Duration of use: 8 hours/day;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Propan-2-ol; EC No. 200-661-7; CAS Nbr 67-63-0;

Exposure Scenario Name	Laboratory Use
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 15 -Use a laboratory reagent ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
Processes, tasks and activities covered	Use as a laboratory reagent.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 4 hours/day;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Professional Laboratory Use
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 15 -Use a laboratory reagent ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
Processes, tasks and activities covered	Use as a laboratory reagent.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Discharge volume of sewage treatment plant: 2,000,000 liters per day; Duration of use: 8 hours/day; Flow rate of receiving surface water:: 18,000 cubic meters per day; Indoors with LEV and good general ventilation; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Incinerate in a facility capable of handling halogenated waste;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and

3M™ Novec™ 72DA Engineered Fluid

PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Professional Use as a Solvent
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing PROC 11 -Non industrial spraying PROC 13 -Treatment of articles by dipping and pouring ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 09a -Widespread use of functional fluid (indoor)
Processes, tasks and activities covered	Cleaning process equipment and parts. Cleaning surfaces by wiping, brushing. Spraying of substances/mixtures. Transfer of substance/mixture with dedicated engineering controls. Transfer of substances/mixtures into small containers e.g. tubes, bottles or small reservoirs.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Indoors with good general ventilation; Medium sized room or workshop (100 m ³ - 500 m ³); Task: Pouring Material - Liquids; Duration of use: 15 min - 1 hour task; Task: Spraying; Duration of use: 15 min - 1 hour task; Task: Wiping Surfaces; Duration of use: 15 min - 1 hour task;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk